

# ICC-ES Report

## PMG-1059

ICC-ES | (800) 423-6587 | (562) 699-0543 | [www.icc-es.org](http://www.icc-es.org)

Reissued 01/2018  
This report is subject to renewal 01/2019

EVALUATION SUBJECT:

**NOBLESEAL<sup>®</sup> TS, NOBLESEAL<sup>®</sup>  
CIS, NOBLESEAL<sup>®</sup> SIS, NOBLE  
DECK<sup>™</sup>, NOBLEFLEX<sup>®</sup>,  
PROBASE<sup>™</sup>, AND VALUESEAL**

**DIVISION:**

22 00 00—PLUMBING

**SECTION:**

22 40 00—PLUMBING FIXTURES

**DIVISION:**

09 00 00—FINISHES

**SECTION:**

09 30 00—TILING

Report Holder:

**NOBLE COMPANY**

7300 ENTERPRISE DRIVE  
SPRING LAKE, MI 49456

Look for the ICC-ES marks of Conformity!



## ICC-ES PMG Product Certificate

**PMG-1059**

Effective Date: January 2018

This listing is subject to re-examination in one year.



[www.icc-es-pmg.org](http://www.icc-es-pmg.org) | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00 — PLUMBING  
Section: 22 40 00 — Plumbing Fixtures

DIVISION: 09 00 00 — FINISHES  
Section: 09 30 00 — Tiling

### Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: NobleSeal® TS, NobleSeal® CIS, NobleSeal® SIS, Noble Deck™, NobleFlex®, ProBase™, and ValueSeal

Listee: Noble Company  
7300 Enterprise Drive  
Spring Lake, Michigan 49456  
[www.noblecompany.com](http://www.noblecompany.com)

### Additional Listee:

Dal-Tile International, Inc.  
7834 C.F. Hawn Freeway  
Dallas, Texas 75217-0130

### Compliance with the following codes:

2018, 2015, 2012, 2009 and 2006 *International Residential Code*® (IRC)  
2018, 2015, 2012, 2009 and 2006 *International Plumbing Code*® (IPC)  
2015, 2012, 2009 and 2006 *Uniform Plumbing Code*\* (UPC)

\*Copyrighted publication of the International Association of Plumbing and Mechanical Officials

### Compliance with the following standard:

TCNA/ANSI A118.10-2014, Specification for Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation.  
ICC-ES AC 115 Acceptance Criteria for Waterproof Membranes for Flooring and Shower Sub-Pan Lining (Editorially revised August 2013)

**Identification:**

NobleSeal® TS, NobleSeal® CIS, NobleSeal® SIS, Noble Deck™, NobleFlex®, ProBase™ and ValueSeal described in this listing must be identified by a stamp bearing the manufacturer's name (Noble Company), the product name (TS, CIS, SIS, Deck, Noble Flex, ProBase, ValueSeal) and the ICC-ES PMG listing mark.

**Installation:**

NobleSeal® TS, NobleSeal® CIS, NobleSeal® SIS, Noble Deck™, NobleFlex®, ProBase™ and Value Seal must be installed in accordance with the manufacturer's published instructions and the applicable code(s).

Ceramic tile must comply with ANSI A137.1.

Drains must have a clamping ring with open weep holes in accordance with ANSI A112.6.3 or have a current ICC-ES PMG listing.

**Models:**

NobleSeal® TS: Composite sheet membrane made from chlorinated polyethylene (CPE), an inherently flexible synthetic elastomer, with fabric laminated to both sides. The product has a nominal thickness of 30 mils [0.030 inch (0.76 mm)] and complies with ANSI A118.10.

NobleSeal® CIS: Same as NobleSeal® TS.

NobleSeal® SIS: Composite sheet membrane made from chlorinated polyethylene (CPE), an inherently flexible synthetic elastomer, with fabric laminated to both sides. The product has a nominal thickness of 50 mils [0.050 inch (1.25 mm)] and complies with ANSI A118.10.

Noble Deck™: Composite sheet membrane made from chlorinated polyethylene (CPE), an inherently flexible synthetic elastomer, with fabric laminated to both sides. The product has a nominal thickness of 40 mils [0.040 inch (1.02 mm)] and complies with ANSI A118.10.

NobleFlex® Drain Flashing: Composite sheet membrane made from chlorinated polyethylene (CPE), an inherently flexible synthetic elastomer, with fabric laminated to both sides. The product has a nominal thickness of 40 mils [0.040 inch (1.02 mm)] and complies with ANSI A118.10.

ProBase™: A waterproof shower base sloped  $\frac{1}{4}$  inch per foot and ready to be tiled. ProBase™ consists of polypropylene honeycomb covered with Noble Deck™.

ValueSeal: Composite sheet membrane made from polyethylene (PE) with fabric laminated to both sides. The product has a nominal thickness of 16 mils [0.016 inch (0.41 mm)] and complies with ANSI A118.10.

**Conditions of Listing:**

1. Application is limited to ceramic tile and dimension stone installations on floors, and as shower sub-pans or lining.
2. Outside the scope of this listing are control joints greater than  $\frac{1}{8}$  inch (3 mm), and structural cracks and expansion joints with vertical differential movement used with NobleSeal® TS, NobleSeal® CIS, NobleSeal® SIS, Noble Deck™, NobleFlex®, ProBase™ and ValueSeal membranes.
3. Noble Company's NobleSeal® TS, NobleSeal® CIS, NobleSeal® SIS, Noble Deck™, NobleFlex®, ProBase™ and ValueSeal membranes are manufactured in Baton Rouge, Louisiana, under a quality control program with annual surveillance inspections by ICC-ES.

**MODEL IDENTIFICATION FOR ADDITIONAL LISTEE MODELS**

<b>NOBLE COMPANY PRODUCTS (LISTED MODELS)</b>	<b>DAL-TILE (ADDITIONAL LISTEE) EQUIVALENT MODELS</b>
NobleSeal <sup>®</sup> TS	Dal-Seal TS
NobleSeal <sup>®</sup> CIS	Dal-Seal CIS
NobleSeal <sup>®</sup> SIS	Dal-Sound
Noble Deck <sup>™</sup>	Dal-Deck
NobleFlex <sup>®</sup>	NA
ProBase <sup>™</sup>	NA
ValueSeal	NA

